



SPORTMOTORCYCLE AG

A-5230 Mattighofen, Tel. 07742/6000-290, Fax 07742/6000-58
FN 116267 g Landesgericht Ried/Innkreis

Vehicle type: KTM LC8

Manufacturer: Behr

only tires with an ECE component type approval are permitted

5.2.1. Nominal rolling circumference:

150/70-18 - 2014 mm

5.2.2. Tyre pressures recommended by the manufacturer:

One driver: front: 240 kPa
rear: 260 kPa

Two driver: front: 240 kPa
Rear: 280 kPa

5.2.3. Tyre/wheel combinations: (see 5.2)

5.2.4. Minimum-speed category symbol compatible with the theoretical maximum
design speed of the vehicle: V (M+S Tires Q with Vmax 160 km/h)

5.2.5. Minimum load-capacity index with the maximum load on each tyre:
front: 54 rear: 70

5.2.6. Categories of use compatible for the vehicle:

radial and diagonal tires

6. Steering

6.1. Steering gear and control

6.1.1. Type of gear: The steering is mounted on the upper fork bridge; mechanical
used steering; steering lock bolts if the steering is moved 30° to the left hand
side.

7. Braking

7.1. Diagram of braking devices: see attachment

7.2. Front and rear brakes, disc and or drum: disc brakes

7.2.1. Make: Brembo

KTM FABAG
HUSABERG FABAG
Zürcherstrasse 305
8500 Frauenfeld
Tel. 052 725 08 88
Fax. 052 725 08 80