



Continental Reifen Deutschland GmbH

Continentalstraße 3-5, 34497 Korbach, Postfach 1120, 34481 Korbach

Phone: +49 - 511 / 938 01, Email: service.motorrad@conti.de

Data sheet No.: 184

Product data for motorcycle tires of the dimension:

90/90V21 M/C (54V) TL

ContiTrailAttack 2

Product Data according to E.T.R.T.O. (European Tyre and Rim Technical Organisation)

Test rim: **2.15x21** Permitted rims: **1.85x21 / 2.15x21 / 2.50x21**

Maximum load at **2,9bar / 42 psi** tire pressure: **212 Kilogramm (Kg)** **467,4 Pound (lb)**

Maximum in Service Overall Width: **99 Millimeter (mm)** **3,90 Inch - Zoll (in)**

Maximum in Service Overall Diameter: **707 Millimeter (mm)** **27,83 Inch - Zoll (in)**

Rolling circumference: **2099 Millimeter (mm)** **82,64 Inch - Zoll (in)**

Static dimension of tire (on the test rim)

Static tire width on test rim: **88 Millimeter (mm)** **3,46 Inch - Zoll (in)**

Static tire diameter on test rim: **698 Millimeter (mm)** **27,48 Inch - Zoll (in)**

Static tire circumference to test rim: **2193 Millimeter (mm)** **86,34 Inch - Zoll (in)**

Maximum speed

Maximum speed for the tire: **260 km/h** **162 mph**

Note:

The Continental assumes no liability in connection with this publication.

Hannover 22.04.2016

Volker Plett

Customer Service M/C Tires